Specification

Model	SH-IDO-3612FH
Air Circulation	Forced
Temp Range	Ambient +10°C to 300°C (Ambient +18°F to 572°F)
Time Range	00.00 to 99HR 59MIN (MIN SEC) Selectable Digital Counter Timer
Temp & Time controller	Microprocess P I D Membrane Touch Digital controller
Heater Capacity	30 KW
Dimension Internal (WxDxH)	2150x1120x1500(mm) 84.65x44.09x59.06(inch)
Dimension External (WxDxH)	2850x1335x2090(mm) 112.20x52.56x82.28(inch)
New Weight	881 Kg
Capacity	3612 L
Material Internal	Stainless Steel
Material External	Steel Plate With Powder Heating Coated
Shelves	6 Supplied (2EAx3, 96 Maximum)
Electrical Requirements 230V ,50/60Hz, 3Φ	79 A
Electrical Requirements 380V ,50/60Hz, 3Φ	46 A

Feature

-Automatic reset function incoming power cut
-Buzzer on when set time arrived
-Fan Motor overload protection
-Electric leakage breaker
-Over temp controller
※We accept custom-made order.

Option

-Programmable controller
-Digital recorder
-2CH Hybrid recorder
-Moving Cart & Room cart
(Accessory will be movable stainless steel plate wide 3EA than 3ea x 2)
-RS-485 interface
-RS-232C interface